



1. Product Name

SLU Primer

Preparation Primer for Self leveling Underlayments

2. Manufacturer

Parexlahabra, Inc.
4125 E La Palma Avenue #250
Anaheim, CA 92807
PH (323) 775-2461
FAX (310) 320-4938
TF (800) 851-6303
www.merkrete.com

3. Product Description

SLU Primer is a uniquely formulated emulsion that must be applied to all substrates prior to the application SLU underlayment.

Features

- Secures bond strength
- Inhibits rapid water loss

4. Technical Data

APPLICABLE STANDARDS

There are no industry standards for this product.

5. Installation

All surfaces must be primed with SLU Primer.

All surfaces to receive SLU must be structurally sound and well bonded to the sub-floor and shall be dry, free of old adhesives, paint, wax, dirt, grease, or any other foreign materials that may inhibit bond before application of the SLU Primer.

Concrete Floors: Prime concrete surfaces, with SLU Primer diluted 1 to 1 with water. Apply a consistent coat using a broom or brush. On extremely porous concrete, two applications recommended. Allow SLU Primer to dry to a tacky surface before applying SLU Leveler.

Plywood: When leveling plywood surfaces prime as follows: dilute SLU Primer at a ratio of 1 gallon of SLU Primer to ½ gallon (1.89L) of water, then mix in 1 ½ gallon (5.68 L) of SLU Underlayment powder. Using a broom or brush, apply primer slurry over the plywood sub-floor. When slurry has dried, fasten galvanized metal lath to the floor.

Special Surfaces: For surfaces like well bonded marble, terrazzo, and existing tile surfaces follow the primer directions above for plywood surfaces. Metal lath is not necessary over existing tile surfaces.

CLEAN UP

Water is only required to remove any uncured mortar from tiles, tools, and equipment.

LIMITATIONS

Do not dilute with water. When using power mixers speed must be no greater than 200 RPM.

Do not use below 40 degrees (F) or above 100 degrees (F). Do not allow final product to freeze for 72 hours. Installations that will be continually wet like swimming pools, fountains, and gang showers, the complete installation should be cured a minimum of 14 days and allowed to dry before exposure to water.

6. Availability

Mer-Krete PUC 1000 caulking is available at leading tile houses and construction distributors. Contact Mer-Krete for the name of the nearest dealer.

7. Warranty

5 year, 10 year and Limited Lifetime warranties are available. Contact Mer-Krete technical department for specific warranty information. Mer-Krete Systems warrants that this product meets applicable ANSI standards in force at the time of manufacture.

8. Maintenance

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. Technical Services

Mer-Krete Systems maintains technical field representatives available throughout the country. Call 1-(800) 851-6303 for the nearest representative.

10. Filing Systems

Mer-Krete Architectural Product information available either in catalog form, or electronically on our website at www.merkrete.com