

Mer-Krete™ Revive

GROUT STAIN AND SEALER

1. PRODUCT NAME

Revive

Grout Stain and Sealer

2. MANUFACTURER

Mer-Krete Systems
501 Van Ness Avenue
Torrance, CA 90501
PH (323) 775-2461
FAX (310) 320-4938
(800) 851-6303
www.merkrete.com

3. PRODUCT DESCRIPTION

BASIC USE

Revive is a pigmented water-based urethane acrylic grout stain and sealer.

FEATURES

It is perfect for revitalizing or changing color of older sanded or non-sanded grouts. **Revive** is designed to help protect against moisture and staining.

4. TECHNICAL DATA

Do not use **Revive** for underwater applications (i.e. pools, tubs, sinks, etc.).

Do not use when temperatures are below 40° F or above 110° F.

Do not allow container to freeze, or get above 110° F.

Avoid scrubbing newly applied stain for 20 days.

(Method of application and grout porosity will vary coverage.)

Wear proper gloves and eye protection.

Do not take internally. If ingested, do not induce vomiting. Seek medical attention.

If contact with eyes or skin occurs, flush with water. If irritation persists, seek medical attention

5. INSTALLATION

PREPARATION

Before attempting to color your grout with **Revive**, test a small area first. Test for previously applied sealers by applying a few drops of water on the grout joint. If the water beads, a sealer is present and must be removed before application of **Revive**. New grout: Allow no less than 7 days curing time before application of **Revive**. All grouts: Surface must be dry, free of oil, grease, dirt, sealers, or any other contaminate. Protect porous tiles to ensure that the grout stain does not penetrate into the tile. Shake well before using. Pour a small amount of **Revive** into a container. Using a bristle or sponge brush, dip into stain and apply a thin coat to grout joint using a back and forth motion. Try to limit the amount of stain on the tile. Wipe off excess immediately with a damp terry cloth towel. Two or more application may be required depending on grout porosity and color. Allow two hour between coats.

4 x 4 tile x 1/4" joint = Approx. 80 sq. ft.

6 x 6 tile x 1/4" joint = Approx. 90 sq. ft.

12 x 12 tile 1/4" joint = Approx. 125 sq. ft.

6. AVAILABILITY

35 Colors in 8 oz. bottles

Mer-Krete Revive is available at leading tile houses and construction distributors. Contact Mer-Krete for the name of the nearest dealer.

Mer-Krete Systems
501 Van Ness Avenue
Torrance, California 90501

Tel: (323) 775-2461
Fax: (310) 320-4938
Internet: www.merkrete.com
E-mail: info@merkrete.com

For the latest and most current product information, make sure to visit our website at: www.merkrete.com

TECHNICAL ASSISTANCE:

Specification assistance is highly recommended prior to a proposed installation. Contact any Mer-Krete technical representative for recommendations over existing substrates or problem areas.



MER-KRETE SYSTEMS
(800) 851-6303

A Division of **PareXLahabra**

REV 7/07

Mer-Krete™ Revive

GROUT STAIN AND SEALER

7. WARRANTY

Mer-Krete warrants that this product meets applicable ANSI standards in force at the time of manufacture. Mer-Krete will replace any product which proves defective due to quality of ingredients used or due to the manufacturing process itself. The warranty shall apply only if the product is installed and used strictly in accordance with applicable industry standards, specifications, and instructions provided by Mer-Krete. Mer-Krete shall not be liable for misapplication, misuse or abuse of the product, application or other event outside of its control. Replacement of defective product or, at Mer-Krete's option, refund of the price of product of any defective item shall be the buyer's sole remedy under this warranty. Mer-Krete shall in no event be liable for any damages in excess of the purchase price of the defective product. MER-KRETE SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES.

This warranty constitutes the sole and exclusive warranty given by Mer-Krete in connection with this product, and Mer-Krete has authorized no person to make or give any other warranties, or representations, oral or written, on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION, WARRANTIES, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification of this warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Mer-Krete.

8. MAINTENANCE

Avoid scrubbing newly applied stain for 20 days. Do not use harsh cleaners. Mild soap and water should be all that is required.

9. TECHNICAL SERVICES

Mer-Krete maintains technical field representatives available throughout the country. For distributor information, call (800) 851-6303.

10. FILING SYSTEMS

Mer-Krete Architectural Product Catalog and CD Rom.
www.merkrete.com

Mer-Krete Systems
501 Van Ness Avenue
Torrance, California 90501

Tel: (323) 775-2461
Fax: (310) 320-4938
Internet: www.merkrete.com
E-mail: info@merkrete.com



MER-KRETE SYSTEMS
(800) 851-6303

A Division of **PareXLahabra**

For the latest and most current product information, make sure to visit our website at: www.merkrete.com

REV 7/07