



# HYDRO GUARD



- ◆ ADHERES TO ALL COMMON SURFACES
- ◆ IAPMO APPROVED
- ◆ WATER AND VAPOR PROOF
- ◆ ANTI-FRACTURE PREVENTION UP TO 1/8" (3 MM)
- ◆ EXCEEDS ANSI A118.10 AND A118.12



# HYDRO GUARD 1

Merkrete Hydro Guard 1 is a thin, load-bearing membrane composed of a modified elastomeric copolymer. With excellent elongation properties and remarkable strength, Hydro Guard 1 provides a 100% waterproof membrane coating while inhibiting the transfer of substrate cracks to the finished overlay. The membrane is installed in a liquid state and can be applied to practically any form or irregular shape (e.g., base flashings, parapets, walls, etc.).

### STANDARDS:

- Exceeds ANSI A118.10 and A118.12
- IAPMO approved

### USES:

- Interior and exterior
- Swimming pools, fountains and water features
- Shower pans, stalls and tubs surrounds
- Industrial, commercial and residential bathrooms and laundries
- Spas and hot tubs
- Kitchens and food processing areas
- Terraces and balconies over unoccupied spaces
- Countertops and façades

### SUITABLE SUBSTRATES:

- Brick masonry
- Cement backer board<sup>1</sup>
- Cement mortar beds
- Cement plaster
- Cement terrazzo
- Ceramic tile and stone
- Concrete
- Concrete masonry
- Exterior grade plywood<sup>2</sup>
- Gypsum wallboard<sup>2</sup>
- Gypsum mortar bed<sup>3</sup>
- Oriented strand board<sup>2</sup>

<sup>1</sup> Consult cement backer board manufacturer for installation recommendations and to verify acceptability for exterior use.

<sup>2</sup> Interior use only.

<sup>3</sup> Requires use of 101 Overspray Primer

### APPROXIMATE COVERAGE:

- 1-gallon unit - 50 sq. ft.
- 3.5-gallon unit - 175 sq. ft.

### ORDERING INFORMATION

Item No.	Size
1802	1 Gal
2591	3.5 Gal

**PAREXUSA**

Parex USA, Inc., a California Corporation

### Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424