



UNDERLAY C MORTAR BED UNDERLAYMENT



- ◆ 1/8"-3" THICKNESS FOR RAMPING, PATCH AND SCREEDING
- ◆ EXCELLENT THERMAL AND ACOUSTICAL INSULATION
- ◆ CRACK RESISTANT; FIRE RETARDANT
- ◆ 6,000 PSI HARDNESS — PERFECT FOR RETAIL AND LIGHT COMMERCIAL



UNDERLAY C

UNDERLAY C provides an optimal surface for floor coverings such as vinyl, resilient tile, carpet, stone, ceramic and quarry tile. It is also exceptional for concrete surface repairs. Underlay C is ideal for achieving a slope base foundation for drainage in showers, drainage under exterior elastomeric deck coatings, or any floor requiring slope for drainage purposes.

SUITABLE SUBSTRATES:

- Cement mortar beds
- Ceramic tile & stone
- Concrete
- Concrete masonry
- Exterior-grade plywood (interior applications)

USES:

- Provides a solid foundation substrate for tile and stone
- Forming ramps and drainage slopes
- Ideal for concrete surface repairs

SUITABLE FLOORING TYPES:

- Carpet
- Wood/Laminate
- VCT
- Sheet vinyl
- Pavers
- Stone

APPROXIMATE COVERAGES

Thickness in Inches	Coverage
1/4"	25 sq. ft.
1/8"	50 sq. ft.

ORDERING INFORMATION

Item#	Size
1879	50-lb. bag

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424