



COLORED CAULKING

SILICONIZED ACRYLIC-BASED CAULKING COMPOUND



- Interior and exterior
- Bonds to most surfaces
- Sanded and smooth textures
- Available in all Color Grout colors in 10.3-oz. tube
- Sanded colored caulking — joint widths from 1/8" to 1/2"
- Smooth colored caulking — joint widths up to 1/8"

1. Product Name

Merkrete PRO MASTIC 400

2. Manufacturer

Parex USA, Inc.

4125 E. La Palma Ave, Suite 250, Anaheim, CA 92807
866-516-0061 • www.merkrete.com

3. Product Description

Merkrete Colored Caulking is an exceptional one-part, siliconized, acrylic-based caulking compound that is mold and mildew resistant. Special chemicals added during manufacturing greatly improve the workability, curing, flexural strength and resistance to a broad spectrum of fungal, algae and bacterial degradation. Colored Caulking is available in a sanded and smooth (non-sanded) formulation in all Merkrete Color Grout colors.

Basic Use

Colored Caulking is used to fill joints between panels, walls and seals around tubs, showers, sinks, countertops, woodwork, baseboards, doors and window frames. It is used where tile meets tile or dissimilar surfaces, like where countertops meet backsplashes or floors meet the walls. Colored Caulking provides exceptional adhesion for ceramic tile, glass, stone, wood and marble vanity tops to their bases. It is ideal for restoring cracked or worn grout joints.

4. Technical Data

Colored Caulking conforms to the requirements for elastic joint sealants, ASTM C920. Follow EJ 171 in the TCNA handbook for treatment of construction, expansion, control and isolation joints when used in a tile installation.

Packaging

10.3-oz. tube / 6 tubes per case | Colors: 30 Colors available in both sanded and smooth versions to coordinate with Merkrete Color Grout.

Shelf Life

Reference Parex USA Expiration Date of Products Technical Bulletin.

5. Installation

Surface Preparation: Surfaces shall be dry, free of adhesives, paint, wax, dirt, grease or any other foreign materials that may inhibit bond. By mechanical means, remove all traces of paint, loose particles, residue and cement particles. Vacuum out joints and wipe them clean with a damp rag.

Application

Insert tube into standard caulking gun. Cut off tip of tube at a slant to desired size. Apply Colored Caulking into opening using a continuous bead. Smooth with a wet putty knife or caulking tool. Unused portion of Colored Caulking should be capped and stored in a cool, dry place and used within one year.

Limitations

Do not use Colored Caulking below 40° F (4° C) or above 95° F (35° C). Use caution — do not allow caulking to freeze for the first 72 hours. Do not use if rain or moisture is expected within 24 hours of application. Colored Caulking may stain porous surfaces like walls. Masking or shielding these areas might be necessary. Test in an inconspicuous area if staining is a concern. Due to the differences in manufacturing and texture, an exact color match to cement grout colors is as near as possible.



Cleaning

Water is all that is needed to remove any Colored Caulking while it is still wet.

6. Availability

Merkrete Colored Caulking is available at leading tile houses and construction distributors. Contact Merkrete or visit our web site for the name of the nearest dealer at www.merkrete.com.

7. Warranty

5-year, 10-year and Limited Lifetime warranties are available. Contact Merkrete Technical Services or visit our website for specific warranty information. Merkrete Systems warrants that this product meets applicable ANSI standards in force at the time of manufacture.

8. Maintenance

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. Technical Services

Merkrete Systems maintains technical field representatives available throughout the country. Call Technical Services at 800-226-2424 for the nearest representative.

10. Filing Systems

Merkrete architectural product information available either in catalog form, or electronically on our website at www.merkrete.com.



Corporate Office
2150 Eastridge Ave
Riverside, CA 92507

www.merkrete.com
866-516-0061

Tech Support: 800-226-2424